

System Data Sheet

Deesa Rubber Corner Guard

(EPDM Rubber)



Description

Deesa Rubber Corner Guard is a rubber guard designed to provide excellent wall protection from vehicles when maneuvering round corners.

Uses

Primarily for use in multi-storey car parks, but can also be applied in loading bays, warehouses and other industrial units.

Benefits

- Provides excellent protection
- Reduces damage to walls
- Weather & UV resistant
- Suitable for indoor and outdoor use
- Good water resistance
- Good impact strength

Color

Available in black color with 3M yellow reflecting sticker.



Deesawala Rubber Industries
5-5-65/S-12A, S.A. Trade Centre, Ranigunj 'X' Road,
Secunderabad-3, Tel: +91 9885634132 / +91 9041421442
Email: murtaza@deesawalarubber.com /
vaibhav@deesawalarubber.com

Technical Information

Specific Gravity	1.45±0.05
Hardness ASTM D2240	Shore A. 75±5
Tensile Strength ASTM D412	12.0 N/mm ²
Elongation at Break ASTM D412	325%, min.
Compression Set ASTM D395	35% (max) at 70 °C for 22 hours
Tear Resistance - Die C ASTM D624	30KN/m, min.
Water Resistance	Yes
Weather Resistance	Yes

Ageing Test (ASTM D573)

Below are the results for the ageing resistance after the duration of the time and temperature

(Ageing Resistance 70hrs @ 100 °C)

Change in Hardness (Points)	+5
Change in Tensile Strength	-25%
Change in Elongation at Break	-22%

Sizes

Available in the following sizes

'L' type 800mm X 100mm X 10mm

'C' type 900mm Length 15mm thick

Material

Natural Rubber / SBR (for exposed decks use EPDM)

Further Information

For other products like Rubber Speed Breaker, Rubber Dock bumper, Rubber Fenders and many more, please contact our team on the number below or visit our website for more details.

www.deesawalarubber.com